

Drift eliminator blade series

Effective reduction of water loss in large cooling towers



Hewitech's blade profiles produced with direct extrusion process as single and stackable profiles in various lengths which allows for a cost optimized shipment to the site. The assembly with distance holders, customized to the individual installation areas in the tower, where round or hindering sectors can be adjusted immediately.

CTI-approved high drift rates, low drop pressure and the specific design generate a proven reduction of water loss in the cooling process.

Features

- Made of PP, solvent free, UV resistant
- Drift rates approved by CTI
- High droplet seperation
- · Very low pressure drop loss
- Drift rates < 0.002%
- · Good mechanical strength
- · Easy and fast installation
- \cdot Optimized handling on site
- Modules adjustable to installation fields







HEWITECH profile drift eliminator system with certified drift rates					
Structure	Code	Material	Spacer single made of PP	Spacer multiple made of PP	Technical Data L x H [mm]
	DEP 156	РР	156-44 / 156-38	156-48 / 156-25	6.000 x 156
	DEP 177	PVC	177-44	177-33	6.000 x 177
	DEP 188	PP / PVC	188-44	none	6.000 x 188

Drift eliminator blade series

This general information about technical data and descriptions of our products has been put together with greatest care. We reserve the rights of any changes without further notice. We recommend to re-check data before using in final project designs. All data without obligations and consequences due to non-compliance.



Hewitech GmbH & Co KG - Am Langenhorster Bahnhof 16 - D-48607 Ochtrup/Germany ♦ +49 2553 97 02 60 · ⊠ info@hewitech.de · ⊕ www.hewitech.de